

**NDB3** - **30** **Z4** **1** - **1** **Q** **H** **Y1** **1** **0** **R**

**Series Name**

**Frame Rating**  
30A

**Tripping Characteristic:**  
**Z2:** DC Short Delay  
**Z4:** DC Medium Delay  
**J2:** AC Short Delay  
**J4:** AC Medium Delay

**Rated Current (A):**  
 1, 2, 3, 4, 5, 6, 8, 10, 12, 15, 16,  
 20, 24, 25, and 30

**Pole Qty:**  
**1:** One Pole

**Mounting:**  
**Q:** Snap In Mounting

**Wiring:**  
**H:** Welded/Connection lug wiring

**Operating Method:**  
**Y1:** Black rocker, vertical white printing  
**Y2:** Black rocker, horizontal white printing  
**Y3:** White rocker, vertical black printing  
**Y4:** White rocker, horizontal black printing  
**Y5:** Orange rocker, vertical black printing  
**Y6:** Orange rocker, horizontal black printing

**Color:**  
**1:** Black  
**2:** Gray

**Accessories:**  
**0:** Without auxiliary contact

**Certification Code:**  
**No code:** TÜV, CE, CCC  
**R:** UL1077, TÜV, CE, CCC  
**L:** UL489A listed, TÜV, CE, CCC(DC Only)