


# M8 Molded Cable Assemblies

Right Angle - Threaded Collar - 3 and 4 Pole  
With PVC, Shielded PVC and PUR Cable



Part Numbers		Length				
		Cable Type	PVC	Shielded PVC	PUR	
		Conductor Size	24 AWG	24 AWG	24 AWG	
<b>3 Pole Male</b>		*9.8' (3M)	08MA3-A3Z	08MA3-Q3Z	08MA3-C3Z	
<b>3 Pole Female</b>		*9.8' (3M)	08FA3-A3Z	08FA3-Q3Z	08FA3-C3Z	
<b>4 Pole Male</b>		*9.8' (3M)	08MA4-A3Z	08MA4-Q3Z	08MA4-C3Z	
<b>4 Pole Female</b>		*9.8' (3M)	08FA4-A3Z	08FA4-Q3Z	08FA4-C3Z	

Technical Information			
Operating Voltage	250 VAC / 300 VDC	Contact Resistance	≤ 6 MΩ
Operating Current	4 A	Male Pin Dimension	1 mm (8 pole = 0.9mm)
Protection Rating	IP 67	Female Contact Material	Phosphorous Bronze
Operating Temperature	-25° C to +85° C	Female Contact Plating	Nickel + 0.3 μm AU Gold
Housing Material	Nylon 6 + 30% Glass fiber	Male Contact Material	Brass
Overmolding Material	Polyurethane	Male Contact Plating	Nickel + 0.3 μm AU Gold

\* Ordering information: Cable length is indicated by the 5th character (example: 08FAX-C3Z)  
Replace the character with the appropriate cable length.

To locate additional product specifications and technical drawings go to [www.asi-ez.com](http://www.asi-ez.com)

[www.asi-ez.com](http://www.asi-ez.com)