



HD Series 40 Position  
Pkg Size:1



HDD Series 72 Position  
Pkg Size:1



HD Series 64 Position  
Pkg Size:1

Description	Type	Order No.	Type	Order No.	Type	Order No.
<b>Male Insert</b>						
Crimp Connection	HD-040-M	2020402101	HDD-072-M	2030722101	HDD-064-M	2020642101
<b>Female Insert</b>						
Crimp Connection	HD-040-F	2020402201	HDD-072-F	2030722201	HDD-064-F	2020642201
<b>Approvals:</b>	UL, CSA					
<b>General Data</b>						
Rated Current (A)		10		10		10
Rated Voltage (V)		600		600		600
UL, CSA						
Mechanical Life Mating Cycles (max)		≤500		≤500		≤500
Temperature Range		-40°C - +125°C		40°C - +125°C		40°C - +125°C
<b>Connection Data</b>						
Wire Range (AWG)		26-14		26-14		26-14
Recommended Tightening Torque (Nm)		-		.5		-
<b>Material Data</b>						
Insert Material		Polycarbonate		Polycarbonate		Polycarbonate
Inflammability class in acc.with UL94		V0		V0		V0
Contact Material		Copper Alloy		Copper Alloy		Copper Alloy
Screw clamp contacts		Silver Plated		Silver Plated		Silver Plated
Crimp contacts		Silver or gold plated		Silver or gold plated		Silver or gold plated
<b>Hoods and Housings</b>						
		H16B Series		H16B series		H24B series