



HDD Series 108 Position
Pkg Size:1



HDD Series 72 Position
Pkg Size:1



HD Series 64 Position
Pkg Size:1

Description	Type	Order No.	Type	Order No.	Type	Order No.
Male Insert						
Crimp Connection	HDD-108-M	2031082101	HDIN80M	2030722101	HDD-064-M	2020642101
Female Insert						
Crimp Connection	HDD-108-F	2031082201	HDIN80M	2030722201	HDD-064-F	2020642201

Approvals: UL, CSA

General Data

Rated Current (A)	10	10	10
Rated Voltage (V)	600	600	600
UL, CSA			
Mechanical Life Mating Cycles (max)	≤500	≤500	≤500
Temperature Range	-40°C - +125°C	40°C - +125°C	40°C - +125°C

Connection Data

Wire Range (AWG)	26-14	26-14	26-14
Recommended Tightening Torque (Nm)	.5	.5	-

Material Data

Insert Material	Polycarbonate	Polycarbonate	Polycarbonate
Inflammability class in acc.with UL94	V0	V0	V0
Contact Material	Copper Alloy	Copper Alloy	Copper Alloy
Screw clamp contacts	Silver Plated	Silver Plated	Silver Plated
Crimp contacts	Silver or gold plated	Silver or gold plated	Silver or gold plated

Hoods and Housings

H24B Series

H16B series

H24B series

