

22mm Push buttons and pilot devices

Control stations - Add-on blocks

Empty control station enclosures



8 L2PP 2A8

Description	Cover color	Catalog number	
For 1 operator	Yellow	8 L2PP 1A5	
For 1 operator	White	8 L2PP 1A8	
For 2 operators	White	8 L2PP 2A8	
For 3 operators	White	8 L2PP 3A8	
For 4 operators	White	8 L2PP 4A8	
For 5 operators	White	8 L2PP 5A8	

General characteristics

Control stations have wire entry through the top or the bottom and come fitted with a conduit (0.84in / 21.3 mm entry diameter).

Operational characteristics

Degree of protection: IP65 using adequate wire glands, not included in the supply, except 8 L2PP 5A8 (IP52 only). Tightening torque of cover fixing screws: 7.1in lb / 0.8 Nm.

Materials

Self-extinguishing ABS plastic.

Complete control stations



8 L2PP 160

Description Enclosure + operator	Catalog number	
8 L2PP 1A8 + 8 LP2T B6244	8 L2PP 100	
8 L2PP 1A8 + 8 LP2T B6344	8 L2PP 110	
8 L2PP 1A5 + 8 LP2T B6344	8 L2PP 115	
8 L2PP 1A8 + 8 LP2T B6544	8 L2PP 120	
8 L2PP 1A5 + 8 LP2T B6644	8 L2PP 130❶	
8 L2PP 1A8 + 8 LM2T B6244	8 L2PP 150	
8 L2PP 1A8 + 8 LM2T B6344	8 L2PP 160	
8 L2PP 1A5 + 8 LM2T B6344	8 L2PP 165	
8 L2PP 1A8 + 8 LM2T B6544	8 L2PP 170	
8 L2PP 1A5 + 8 LM2T B6644	8 L2PP 180❶	

❶ Red mushroom head, twist to release, yellow cover (EN418 compliant), no label and no label holder.

General characteristics

Control stations are supplied assembled and complete with the indicated push-button operator, mounting adapter, legend holder, "STOP" label (except for L2PP 155, L2PP 130, L2PP 165 and L2PP 180) and one NC auxiliary contact. Control stations have wire entry through the top of the bottom and come fitted with a fairlead (0.84in / 21.3 mm entry diameter).

Operational characteristics

Degree of protection: IP65 using adequate wire glands, not included in the supply. Tightening torque of cover fixing screws: 7.1in lb / 0.8 Nm.

Materials

Self-extinguishing ABS plastic.

To locate additional product specifications and technical drawings go to www.asi-ez.com