

Monoblock LED pilot lights

Plastic series



Order code	Voltage	LED colour	Qty per pkg	Weight
	[V]		n°	[kg]
8 LP2T ILB3	24VAC/DC	Green	10	0.021
8 LP2T ILB4		Red	10	0.021
8 LP2T ILB5		Yellow	10	0.021
8 LP2T ILB6		Blue	10	0.021
8 LP2T ILB8		White	10	0.021
8 LP2T ILE3		110VAC	Green	10
8 LP2T ILE4	Red		10	0.024
8 LP2T ILE5	Yellow		10	0.024
8 LP2T ILE6	Blue		10	0.024
8 LP2T ILE8	White		10	0.024
8 LP2T ILM3	230VAC	Green	10	0.024
8 LP2T ILM4		Red	10	0.024
8 LP2T ILM5		Yellow	10	0.024
8 LP2T ILM6		Blue	10	0.024
8 LP2T ILM8		White	10	0.024

Operational characteristics

- Operating voltage: 24VAC/DC
110VAC
230VAC
- Electric life: >30,000 hours
- Screw termination
- Maximum tightening torque: 0.8Nm
- Side cable entry
- Ambient operating temperature: -5...+40°C
- Degree of protection: IP65.

Maximum conductor cross section


1 or 2 1.5mm² or AWG 16 cables.

Wiring diagram



Certification and compliance

Certifications obtained: cULus.
Compliant with standards: IEC/EN 60947-1,
IEC/EN 60947-5-1.



To locate additional product specifications and technical drawings go to www.asi-ez.com