








M8 Cable Assembly, Male Connectors, Unshielded PVC Cable



Technical drawing							
							
Product description							
Connector type	Circular connector with moulded cable		Circular connector with moulded cable		Circular connector with moulded cable		
Conforms to	IEC 61076-2-104		IEC 61076-2-104		IEC 61076-2-104		
Construction type	M8 A -Coding		M8 A -Coding		M8 A -Coding		
Description	Circular connector M8 series with moulded cable		Circular connector M8 series with moulded cable		Circular connector M8 series with moulded cable		
Part number	08MD3A1Z	08MA3A1Z	08MD4A1Z	08MA4A1Z	08MD8K1Z	08MA8K1Z	
Housing type	Straight 180°	Angled 90°	Straight 180°	Angled 90°	Straight 180°	Angled 90°	
Cable gland	Moulded cable		Moulded cable		Moulded cable		
Contacts type	Male		Male		Male		
Number of contacts	3poles		4poles		8poles		
Housing colour	Black		Black		Black		
Technical data							
Type of termination	Contacts to crimp wires		Contacts to crimp wires		Contacts to solder wires		
Contacts material	Brass + Gold flash		Brass + Gold flash		Brass + Gold flash		
Coupling nut type	Knurl round		Knurl round		Knurl round		
M8 coupling nut material	Brass + Nickel plated		Brass + Nickel plated		Brass + Nickel plated		
M8 coupling nut torque	0.2 N*m		0.2 N*m		0.2 N*m		
Rated voltage	50V AC/ 60V DC		50V AC/ 60V DC		30V AC/DC		
Rated current	3A		3A		1.5A		
O-ring material	-		-		-		
Cable type	PVC/PVC CEI2022		PVC/PVC CEI2022		PVC/PVC CEI2022		
Cable jacket colour	Black		Black		Black		
No. Conductors / Section	3x0.25mm ²		4x0.25mm ²		8x0.14mm ²		
Conductor colours	Brown; Blue; Black		Brown; White; Blue; Black		White; Brown; Green; Yellow; Grey; Pink; Blue; Red		
Cable diameter	ø4mm (±0.3)		ø4.4mm (±0.3)		ø4.9mm (±0.3)		
Cable length	1m		1m		1m		
Packaging							
Qty/Bag	1 pc / bag		1 pc / bag		1 pc / bag		
Other accessories options							
See accessories section							
Notes:							
Connectors available with different features: See the general features and codification scheme page See the cables list section							