



- Snap-on design allows for mounting on the standard DIN rails for easy installation
- Interlocking feature for additional stability
- Locking washer for assured connection
- Center snap in labelling strip allows for easy circuit identification to simplify wiring
- Snap on covers provide total insulation and side jumpers ease circuit cross connection
- Multiple wire models for power distribution and double levels for space saving are available
- Models are UL approved, 10 to 309 amps, 600V

Ordering Info					
Order #	ASI391001	ASI391002	ASI391003	ASI391004	ASI391005
Type	ASIUTD-10	ASIUTD-15	ASIUTD-24	ASIUTD-32	ASIUTD-41
Specifications					
Dimensions (DxWxH) mm	40/7.3/29	40/8/29	40/9.5/29	40/11.5/29	46/14.5/34
Screw Size	M3	M3.5	M3.5	M4	M5
Voltage Rating (V)	600	600	600	600	600
Current Rating (Amps)	10	15	20	30	50
Color	Black	Black	Black	Black	Black

Accessories					
	Order #	Order #	Order #	Order #	Order#
End Stop	ASIUD1B	ASIUD1B	ASIUD1B	ASIUD1B	ASIUD1B
DIN Rail (2 Meters) 7.5 x 35mm slotted	PR005	PR005	PR005	PR005	PR005
End Cover	ASI392001	ASI392001	ASI392001	ASI392001	ASI392002
Marking Labels	ASI394006	ASI394006	ASI394006	ASI394006	ASI394006
Jumpers 2pos 4pos 10pos	ASI393001 ASI393003 ASI393006	ASI393007 ASI393009 ASI393012	ASI393013 ASI393015 ASI393018	ASI393019 ASI393021 ASI393024	ASI393025 ASI393027 ASI393030
Dust Cover	ASI395001	ASI395001	ASI395001	ASI395001	ASI395002