



- Slide-On technology for secure installation on standard DIN rails
- Interlocking feature for additional stability
- Center snap in labelling strip allows for easy circuit identification to simplify wiring
- Snap on covers provide total insulation and side jumpers ease circuit cross connection
- Locking washer for assured connection
- Multiple wire models for power distribution and double levels for space saving are available
- Models are UL approved, 10 to 309 amps, 600V

Ordering Info			
Order #	ASI391006	ASI391007	ASI391008
Type	ASIUTD-63	ASIUTD-100	ASIUTD-150
Specifications			
Dimensions (DxWxH) mm	54/19.5/38	72/27/45	76/28/51
Screw Size	M6	M8	M8
Voltage Rating (V)	600	600	600
Current Rating (Amps)	90	130	175
Color	Black	Black	Black

Accessories			
	Order #	Order #	Order #
End Stop	ASIUD1B	ASIUD1B	ASIUD1B
DIN Rail (2 Meters) 7.5 x 35mm slotted 7.5 x 35mm non-slotted 15 x 35mm slotted 15 x 35mm non-slotted	PR005 PR003 PR006 PR007	PR005 PR003 PR006 PR007	PR005 PR003 PR006 PR007
Marking Label	ASI394006	ASI394006	ASI394006
Dust Cover	ASI395003	ASI395004	ASI395004
End Cover	ASI392003	ASI392004	ASI392005