

18.0 V Cordless Hydraulic Crimping Tool B 15MA

B 15MA

general features



Crimping force tons	Dimensions in.			Battery Li-Ion	Weight lbs. (with battery)
	length	height	width		
1.7	13.3	5.3	3.2	18.0V 2.0Ah	3.8

**18.0V
2.0Ah
Li-Ion**



New

Can be operated with one hand. Balanced for greater control. Head rotates by 340° for ease of operation in confined spaces. The tool is fitted with a maximum pressure valve. Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions. New Li-Ion 18V 2Ah High Power battery. The battery is equipped with led indicators that indicate the remaining battery life at any time by pressing the adjacent button. Supplied in a robust plastic case to accommodate the tool and all the accessories.

Two batteries and AC charger (110-115V) included. Many different interchangeable crimping dies available.

MAIN APPLICATIONS - max size AWG		
Copper lugs and splices	Insulated terminals	End sleeves
22 - 6	22 - 6	22 - 2

STORAGE				
Type	Dimensions in.	Weight lbs.	Supplied with the tool	Purchase separately
VAL P22	18.3x12.4x4.6	3.3	*	—

The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- AC charger (110-115V)
- Plastic carrying case suitable for storing the tool and accessories



**NEW
18V Li-Ion
BATTERY**

Operating temperature: +5 to +122°F

Available also:

B15MA-WS, with wire stop and connector positioner



B15MA-WS, head detail

DIE SELECTOR CHART			
Conductor Size (AWG)	Connector Type (A-M)	Die Set	Crimp Shape
22-16	A03	MA03/3-15	Indent
16-8	A06-A2	ME03/2-15	Hex
8-6	A2-A3	ME2/3-15	Hex



Battery led indicators



Interchangeable die sets



switch ergonomically designed



Slot-in battery with release button