



Miniature, Multi-Position Fixed PCB Terminal Blocks

The CPA is a single sub-miniature printed circuit board terminal block that is available in several pin spacings and from 1 to 24 positions. The CPA uses a moving metal body design for the termination of the wire to insure maximum reliability. The CPA is UL recognized and will terminate wire ranging from 16 to 30 A WG and will handle 10 amps at 300 volts. The CPA is available in a right angle version. The standard color is green, however several other colors are available upon request.



SPECIFICATIONS

Housing Material:	PA68 Polyimide, Flammable UL94V0
Housing Color:	Green
Screw:	Zinc Plated Steel
Clamp:	Nickel Plated Brass
Pin:	Tin Plated Brass
Testing torque:	2.7 in/lb
Wire range:	16-30 AWG
P.C.B. mounting hole:	1.1mm
Nominal current:	10 A
Voltage:	300 V
Temperature Range:	-30° C to 110° C



Catalog #	No. of Positions	Length (mm)
CPA3.5-2SQVE	2	7
CPA3.5-3SQVE	3	10.5SQ
CPA3.5-4SQVE	4	14
CPA3.5-5SQVE	5	18.5
CPA3.5-6SQVE	6	21
CPA3.5-7SQVE	7	24.5
CPA3.5-8SQVE	8	28
CPA3.5-9SQVE	9	31.5
CPA3.5-10SQVE	10	35
CPA3.5-11SQVE	11	38.5
CPA3.5-12SQVE	12	42
CPA3.5-13SQVE	13	45.5
CPA3.5-14SQVE	14	49
CPA3.5-15SQVE	15	52.5
CPA3.5-16SQVE	16	56
CPA3.5-17SQVE	17	59.5
CPA3.5-18SQVE	18	63
CPA3.5-19SQVE	19	66.5
CPA3.5-20SQVE	20	70
CPA3.5-21SQVE	21	73.5
CPA3.5-22SQVE	22	77
CPA3.5-23SQVE	23	80.5
CPA3.5-24SQVE	24	84

To locate additional product specifications and technical drawings go to www.asi-ez.com