

# 5.08mm Pluggable Terminal Blocks

## SPECIFICATIONS

|                    |                                  |
|--------------------|----------------------------------|
| Housing Material:  | PA68 Polyamide, Flammable UL94V0 |
| Housing Color:     | Green                            |
| Screw:             | Zinc Plated Steel                |
| Clamp:             | Nickel Plated Brass              |
| Pin:               | Tin Plated Brass                 |
| Testing torque:    | 4.4 in/lb.                       |
| Wire range:        | 12-24 AWG                        |
| Nominal current:   | 12 A                             |
| Voltage:           | 300 V                            |
| Temperature Range: | -30° C to 85° C                  |



Part#                      #of Positions

|              |    |
|--------------|----|
| CPF5.08-2FV  | 2  |
| CPF5.08-3FV  | 3  |
| CPF5.08-4FV  | 4  |
| CPF5.08-5FV  | 5  |
| CPF5.08-6FV  | 6  |
| CPF5.08-7FV  | 7  |
| CPF5.08-8FV  | 8  |
| CPF5.08-9FV  | 9  |
| CPF5.08-10FV | 10 |
| CPF5.08-11FV | 11 |
| CPF5.08-12FV | 12 |
| CPF5.08-13FV | 13 |
| CPF5.08-14FV | 14 |
| CPF5.08-15FV | 15 |
| CPF5.08-16FV | 16 |
| CPF5.08-17FV | 17 |
| CPF5.08-18FV | 18 |
| CPF5.08-19FV | 19 |
| CPF5.08-20FV | 20 |
| CPF5.08-21FV | 21 |
| CPF5.08-22FV | 22 |
| CPF5.08-23FV | 23 |
| CPF5.08-24FV | 24 |

