




With special connections

with UL94V-0 polyamide insulating body

- with flat push-on tab connections
- universal mounting onto both PR/DIN and PR/3 type rails - according to IEC 60715 Std., "G32" and "TH/35" types
- available in grey RAL 7042 and beige RAL 1001 colours (where indicated)



Cross-connection possibility

6.3 x 0.8 mm, or 2.8 x 0.8 mm, flat push-on tab connections acc. to standard IEC 60760

6.3 x 0.8 mm, or 2.8 x 0.8 mm, flat push-on tab connections acc. to standard IEC 60760

The /GR tag indicates the grey colour version.

grey version	
beige version	
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm ²)
connecting capacity	
flexible	(mm ²)
rigid	(mm ²)
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / recommended)	(Nm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

PDF.2	
Cat. No.	PF100
feed-through with push-on tab connections	
rated cross-section	2,5
connecting capacity	
flexible	up to 2,5
rigid	-
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	630 V / 20 A / -
rated voltage / rated current / AWG / tightening torque value	600 V / 16 A / 20-10 AWG
(Ex e) rated voltage	-
rated impulse withstand voltage / pollution degree	6 kV / 3
insulation stripping length	-
tightening torque value (test / recommended)	-
height / width / thickness	50 / 57 / 6,5
height / width / thickness	58 / 57 / 6,5
height / width / thickness	54 / 57 / 6,5

FDP.2/GR	
Cat. No.	FD100GR
FDP.2	
Cat. No.	FD100
feed-through with push-on tab connections	
rated cross-section	2,5
connecting capacity	
flexible	up to 2,5
rigid	-
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	800 V / 20 A / -
rated voltage / rated current / AWG / tightening torque value	600 V / 16 A / 20-10 AWG
(Ex e) rated voltage	-
rated impulse withstand voltage / pollution degree	8 kV / 3
insulation stripping length	-
tightening torque value (test / recommended)	-
height / width / thickness	49 / 65,5 / 6,5
height / width / thickness	57 / 65,5 / 6,5
height / width / thickness	53 / 65,5 / 6,5

CVF.4	
Cat. No.	CV100
CVF.4 (Ex)i	
Cat. No.	CV200
feed-through, 1 screw + 3-push-on connections	
rated cross-section	4
connecting capacity	
flexible	0,2 ÷ 6
rigid	0,2 ÷ 6
max. flexible with ferrule (mm ²)-ferrule type	4 - WP40/16
rated voltage / rated current / gauge	800 V / 20 A / A4
rated voltage / rated current / AWG / tightening torque value	600 V / 20 A / 20-12 AWG / 0,5 Nm
(Ex e) rated voltage	-
rated impulse withstand voltage / pollution degree	8 kV / 3
insulation stripping length	11
tightening torque value (test / recommended)	-
height / width / thickness	52 / 48,5 / 6
height / width / thickness	60 / 48,5 / 6
height / width / thickness	56 / 48,5 / 6

APPROVALS



ACCESSORIES	
End sections	grey beige blue
Permanent cross connection (pre-assembled)	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Cover for cross-connection	
Warning plate	
Marking tag	printed or blank
End bracket	
Mounting rail	
according to IEC 60715 Std.	

Type	Cat. No.
PDF/PT	PF101
-	
-	
-	
DFU/5	DU05..
-	
-	
SNZ/65	SN006
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

Type	Cat. No.
FDP/PT/GR	FD101GR
FDP/PT	FD101
PH/2,5-4	PH100
-	
-	
DFU/5	DU05..
-	
-	
SDD/1	DD001
SNZ/60	SN007
-	
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

Type	Cat. No.
CVF/PT	CV101
CVF/PT (Ex)i	CV201
PM/40/2 poles	PM402
PM/58/3 poles	PM583
PM/58/5 poles	PM585
PM/58/10 poles	PM580
-	
PMP/58	PMP58
CPM/12i	CPM12
DFU/3	DU03..
-	
PSD/A	PD001
SDD/1	DD001
SNZ/60	SN007
-	
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005