



HD Series 50 Position
Pkg Size:1



HDD Series 24 Position
Pkg Size:1



HDD Series 42 Position
Pkg Size:1

Description	Type	Order No.	Type	Order No.	Type	Order No.
Male Insert Crimp Connection	25x2 Male Insert	HDIN50M	HDD-024-M	2030242101	HDD-042-M	2030422101
Female Insert Crimp Connection	25x2 Female Insert	HDIN50F	HDD-024-F	2030242201	HDD-042-F	2030422201
Approvals:	CSA					
General Data						
Rated Current (A)	10		10		10	
Rated Voltage (V) UL, CSA	600		600		600	
Mechanical Life Mating Cycles (max)	≤500		≤500		≤500	
Temperature Range	-40°C - +125°C		40°C - +125°C		40°C - +125°C	
Connection Data						
Wire Range (AWG)	26-14		26-14		26-14	
Recommended Tightening Torque (Nm)	-		.5		.5	
Material Data						
Insert Material	Polycarbonate		Polycarbonate		Polycarbonate	
Inflammability class in acc.with IEC 94	V0		V0		V0	
Contact Material	Copper Alloy		Copper Alloy		Copper Alloy	
Screw clamp contacts	Silver Plated		Silver Plated		Silver Plated	
Crimp contacts	Silver or gold plated		Silver or gold plated		Silver or gold plated	
Heads and Housings	H32A Series		H6B series		H10B Series	