

Switch disconnectors

16A to 125A switch disconnectors

Three-pole switch disconnectors in housing

2



GAZ016...-GAZ040...



GAZ063...-GAZ125...

Order code	Conventional free air thermal current Ith AC21A	Qty per pkg	Wt
	[A]	n°	[kg]
With rotating red/yellow handle.			
GAZ016	16	1	0.450
GAZ025	25	1	0.450
GAZ032	32	1	0.450
GAZ040	40	1	0.450
GAZ063	63	1	2.220
GAZ080	80	1	2.220
GAZ100	100	1	2.220
GAZ125	125	1	2.220
With rotating black handle.			
GAZ016 B	16	1	0.450
GAZ025 B	25	1	0.450
GAZ032 B	32	1	0.450
GAZ040 B	40	1	0.450
GAZ063 B	63	1	2.220
GAZ080 B	80	1	2.220
GAZ100 B	100	1	2.220
GAZ125 B	125	1	2.220

Empty enclosures



GAZ1...



GAZ3...

Order code	Characteristics	Qty per pkg	Wt
		n°	[kg]
For switch disconnectors.			
With rotating red/yellow handle. Complete with shaft extension.			
GAZ1	For GA016 A-GA040 A and GA040 D	1	0.320
GAZ3	For GA063 A-GA125 A, GA080 D and GA125 D	1	1.900
With rotating black handle. Complete with shaft extension.			
GAZ1 B	For GA016 A-GA040 A and GA040 D	1	0.320
GAZ3 B	For GA063 A-GA125 A, GA080 D and GA125 D	1	1.900

Components Enclosure	Switch disconnector	Handle
GAZ1	GA016 A	GAX61
GAZ1	GA025 A	GAX61
GAZ1	GA032 A	GAX61
GAZ1	GA040 A	GAX61
GAZ3	GA063 A	GAX61
GAZ3	GA080 A	GAX61
GAZ3	GA100 A	GAX61
GAZ3	GA125 A	GAX61
GAZ1 B	GA016 A	GAX61 B
GAZ1 B	GA025 A	GAX61 B
GAZ1 B	GA032 A	GAX61 B
GAZ1 B	GA040 A	GAX61 B
GAZ3 B	GA063 A	GAX61 B
GAZ3 B	GA080 A	GAX61 B
GAZ3 B	GA100 A	GAX61 B
GAZ3 B	GA125 A	GAX61 B

General characteristics

- Polycarbonate housing material
- For four-pole version, add fourth pole GAX4...A
- One auxiliary contact block can be fitted on the right and left sides of the disconnector
- Padlockable handle
- Sealable cover
- IP65 degree of protection
- Entries
 - GAZ016...-GAZ040...: PG16/M25 and PG13.5/M20 knockouts
 - GAZ063...-GAZ125...: smooth surface to be drilled by the user
 - GAZ1...: PG16/M25 and PG13.5/M20 knockouts
 - GAZ3...: smooth surface to be drilled by the user

The empty enclosures are supplied with the following accessories:

Enclosure	GAZ1 B	GAZ3 B	GAZ 1	GAZ 3
Black handle GAX61 B	1	1	—	—
Red/yellow handle GAX61	—	—	1	1
Shaft extension	1	1	1	1
Neutral terminal	1	—	1	—
Earth terminal	1	—	1	—

Reference standards

Compliant with standards: IEC/EN 60947-3, IEC7EN 60947-1.

Special GAZ... versions

In addition to the standard-supplied types, cULus certified versions are available. Add suffix **UL** at the end of the order code; e.g. GAZ063 B **UL**.