

# HPC Series







## with polyamide insulating body

- UL94V-0
- panel mount by means of clips
- panel thickness 0,6 ÷ 1,2 mm
- fixing hole Ø 3,5 mm
- available in standard (grey RAL 7042 colour) or (Ex) i “intrinsic safety” circuits (blue RAL 5015 colour) versions, where indicated






Modular test plug



PTC jumper configurations					
SINGLE OR PARALLEL EXTENDING	POLE SKIPPING	ADJACENT WITHOUT BARRIER	ADJACENT WITH BARRIER	STAGGERED MODE	PARALLEL SKIPPING
					
Insulation voltage in the above configurations (V)					
400	400		800 (PT)	400	400

The /GR tag indicates the grey colour version.



grey version	
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm <sup>2</sup> )
connecting capacity	
flexible	(mm <sup>2</sup> )
rigid	(mm <sup>2</sup> )
max. flexible with ferrule (mm <sup>2</sup> )-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG	UL
(Ex e) rated voltage  / 	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	 TH/15 5,5 mm

<b>HPC.2/GR</b>	Cat. No. <b>HP160GR</b>
<b>HPC.2 (Ex)i</b>	Cat. No. <b>HI131</b>

passante	
2,5	
0,2 ÷ 4	
0,2 ÷ 4	
2,5 - WP25/14	
800 V / 24 A / A3	
600 V / 24 A / 24-12 AWG	
(*)	
8 KV / 3	
13	
-	
30 / 36 / 5,2	



### APPROVALS

ACCESSORIES	
End sections	grey blue
Permanent cross connection (intrinsically IPXXB protected once mounted)	
Rated current carrying capacity of jumper	(A)
Cross connection identification strip (100 mm)	green
Coloured partition	red, green, white
Numbering strip	
Screwdriver for the activation of the spring	
Modular test plug	
End section for modular test plug	
Test plug	
End bracket	
Mounting rail according to IEC 60715 Std.	
	

Type	Cat. No.
HPV/PT/GR	HV111GR
-	
PTC/03/02 poles	PTC0302
PTC/03/03 poles	PTC0303
PTC/03/05 poles	PTC0305
PTC/03/10 poles	PTC0310
PTC/03/00 (47 poles)	PTC0300
24	
PTC/SP	PTC0990
DFP/2	DH02..
SHZ/2	SH001
CCH/2,5-4	CCH02
SDH/5	DH005
SH5/PT	DH501
SDD/1	DD001
BT/2 for PR/2 only	BT006
-	
-	
PR/2/AC of steel	PR009
PR/2/AS same with slots	PR010

In electrical panels where the space is particularly limited but there is nevertheless the requirement of high cable connection density, Cabur offers, also in spring-clamp technology, a series of mini terminal blocks suited for the connection of conductors up to 4 mm<sup>2</sup>.

The range consists of three versions, for panel mount (by means of screw or clip) and for the IEC 60715, 15 mm PR/2 rail mount.

The particular configuration of the insulating body of the three types of terminal blocks allows the perfect matching between anyone of them, even of different versions, in order to guarantee maximum flexibility.