

Max Ambient Temperature -25../..+150°C

..KRIZ M30 HT SENSOR..

IN1530HTS150

Sensor Size	M30
Nominal Sensing Distance (SN)	15mm EN-50010
Amplifier <i>Note 1*</i>	Built-In
Installation	Non-Flush
Supply Voltage Range <i>Tech-note 1*</i>	10../..30 VDC
Rated Supply Voltage	24 VDC
No Load (<i>I</i>)	≤ 3mA
Output (PNP .or. NPN)	N.O. .or. N.C.
Max (<i>I</i>) Output <i>Tech-note 2*</i>	150mA@24VDC
Max Switching Frequency	200Hz@150°C
Voltage Drop (<i>Output</i>)	≤ 1.8VDC
Repeatability	< 3% of SN
Hysteresis	3....15% of SN
Target LED	N/A
Connecting cable <i>Tech-note 3*</i>	Silicone .or. Teflon
Connector Option	Yes
Environmental Protection	IP66
Fastner Torque Value	40Nm
Housing Material	1.4305 St Stl



Notes...

*1**- All kriz sensor products that operate up to and including 180C are manufactured with a built in amplifier and come fully calibrated with no user adjustments required..

*Tech-note 1**

This sensor incorporates reverse polarity protection.


*Tech-note 2**

The output stage of the sensor is protected against overload and short circuit condition.

*Tech-note 3**

All kriz sensor products operate independant of cable length which may be altered to suit the application without any effect on calibration etc.

..DIMENSIONAL DATA..



www.asi-ez.com
877-650-5160

PO Box 1340 Mechanicsburg PA 17055