


Disconnect

with UL94V-0 polyamide insulating body

- disconnect with special connections
- possibility to perform cross-connections
- available in standard (grey RAL 7042 and beige RAL 1001 colours) or (Ex)i "intrinsic safety" circuits (blue RAL 5015 colour) versions
- universal mounting onto both PR/DIN and PR/3 type rails - according to IEC 60715 Std., "G32" and "TH/35" types
- "Easy Bridge" system: multi-pole cross-connection without the need of additional protection

with 1 screw and 1 solder connection,
4 x 0.8 mm



PTC jumper configurations					
SINGLE OR PARALLEL EXTENDING	POLE SKIPPING	ADJACENT WITHOUT BARRIER	ADJACENT WITH BARRIER	STAGGERED MODE	PARALLEL SKIPPING

Terminal block	Jumper	Insulation voltage in the above configurations (V)			
MPS.4	PTC/4	400	400	400	400
DSS.4	PTC/4	400	400	400	400

The /GR tag indicates the grey colour version.

grey version	
beige version	
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm ²)
connecting capacity	
flexible	(mm ²)
rigid	(mm ²)
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL (Ex e) rated voltage (V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / recommended)	(Nm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

MPS.4/GR	
Cat. No.	MP950GR
MPS.4	
Cat. No.	MP950
MPS.4/SW (Ex)i	
Cat. No.	MP960
disconnect lever	4
flexible	0,2 ÷ 6
rigid	0,2 ÷ 6
max. flexible with ferrule	4 - WP40/16
rated voltage / rated current / gauge	400 V / 24 A / A4
rated voltage / rated current / AWG / tightening torque value	600 V / 24 A / 26-10 AWG / 0,5 Nm
rated impulse withstand voltage / pollution degree	6 kV / 3
insulation stripping length	9
tightening torque value (test / recommended)	0,5 / 1,2
height / width / thickness	47 / 47 / 6
height / width / thickness	55 / 47 / 6
height / width / thickness	51 / 47 / 6

MPS.4/VS	
Cat. No.	MP930
disconnect lever with 1 screw and 1 solder connect.	4
flexible	0,2 ÷ 6
rigid	0,2 ÷ 6
max. flexible with ferrule	4 - WP40/16
rated voltage / rated current / gauge	400 V / 20 A / A4
rated voltage / rated current / AWG / tightening torque value	600 V / 24 A / 26 ÷ 10 AWG / 0,5 Nm
rated impulse withstand voltage / pollution degree	4 kV / 3
insulation stripping length	9
tightening torque value (test / recommended)	0,5 / 1,2
height / width / thickness	47 / 47 / 6
height / width / thickness	55 / 47 / 6
height / width / thickness	51 / 47 / 6

DSS.4/GR	
Cat. No.	DS400GR
DSS.4	
Cat. No.	DS400
disconnect lever	2 levels, with upper disconnect level
flexible	0,2 ÷ 6
rigid	0,2 ÷ 6
max. flexible with ferrule	4 - WP40/16
rated voltage / rated current / gauge	400 V / 24-32 A (*) / A4
rated voltage / rated current / AWG / tightening torque value	300 V / 24-32 A / 26-10 AWG / 0,5 Nm
rated impulse withstand voltage / pollution degree	4 kV / 3
insulation stripping length	9
tightening torque value (test / recommended)	0,5 / 1,2
height / width / thickness	68 / 78 / 6
height / width / thickness	75 / 78 / 6
height / width / thickness	72 / 78 / 6

APPROVALS



other approvals referred to MPS.4 standard version

ACCESSORIES

End sections	grey beige blue
Permanent cross connection (pre-assembled) (intrinsically IPXXB protected once mounted)	
Rated current carrying capacity of jumper	(A)
Cross-connection identification strip (100 mm)	green
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Cover for cross-connection	red, blue or white
Marking tag	printed or blank
End bracket	
Mounting rail according to IEC 60715 Std.	

Type	Cat. No.
MPS.4/PT/GR	MP901GR
MPS.4/PT	MP901
MPS.4/PT (Ex)i	MP902
PTC/4/02 poles	PTC0402
PTC/4/03 poles	PTC0403
PTC/4/05 poles	PTC0405
PTC/4/10 poles	PTC0410
PTC/4/00 (42 poles)	PTC0400
32	
PTC/SP	PTC0990
-	
DFU/3	DU03..
DFM/500	DF500
-	
SNZ/60	SN007
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

Type	Cat. No.
-	
MPS.4/PT	MP901
PTC/4/02 poles	PTC0402
PTC/4/03 poles	PTC0403
PTC/4/05 poles	PTC0405
PTC/4/10 poles	PTC0410
PTC/4/00 (42 poles)	PTC0400
32	
PTC/SP	PTC0990
-	
DFU/3	DU03..
DFM/500	DF500
-	
SNZ/60	SN007
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

Type	Cat. No.
DSS/PT/GR	DS301GR
DSS/PT	DS301
PTC/4/02 poles	PTC0402
PTC/4/03 poles	PTC0403
PTC/4/05 poles	PTC0405
PTC/4/10 poles	PTC0410
PTC/4/00 (42 poles)	PTC0400
32	
PTC/SP	PTC0990
-	
DFU/7	DU07..
DFM/500	DF500
-	
SNZ/60	SN007
-	
CNU/8-CSC	NU...-CS...
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

(*) values referred to the upper and lower conducting body, respectively

To locate additional product specifications and technical drawings go to www.asi-ez.com