

Pg thread DIN 40 430

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1910.07	Pg 7	12,5	2 - 5	15	8	18-22	100
1910.09	Pg 9	15,5	2 - 6	19	8	22-26	100
1910.11	Pg11	19	4 - 7	22	8	23-28	100
1910.13	Pg13,5	20,5	5-10	24	9	24-29	100
1910.16	Pg16	22,5	6-12	27	10	26-31	50
1910.21	Pg21	29	9-15	33	12	30-35	50
1910.29	Pg29	37	12-20	42	12	33-39	25
1910.36	Pg36	47	18-26	53	14	42-49	10
1910.42	Pg42	54	25-31	60	14	42-50	5
1910.48	Pg48	60	27-39	66	15	45-55	5

Add to Ref. N for Black



Material: POLYAMIDE PA6.6
 self-extinguishing class V2 (UL 94)
 Temperature range:
 -20°C to +90°C (continuous)
 Sealing ring: NEOPRENE® 50 sh A
 Protection: IP 68
 Colour: RAL 7035 light grey,
 RAL 9005 black, RAL 7001 dark
 grey

MAXIblock® *extended thread*
Pg thread DIN 40 430

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1901.07	Pg 7	12,5	3,5- 7	15	15	18-22	100
1901.09	Pg 9	15,5	5 - 8	19	15	22-26	100
1901.11	Pg11	19	5 -10	22	15	23-28	100
1901.13	Pg13,5	20,5	7 -12	24	15	24-29	100
1901.16	Pg16	22,5	10 -14	27	15	26-31	50
1901.21	Pg21	29	13 -18	33	15	30-35	50
1901.29	Pg29	37	18 -25	42	15	33-39	25
1901.36	Pg36	47	20 -32	53	18	42-49	10
1901.42	Pg42	54	28 -38	60	18	42-50	5
1901.48	Pg48	60	37 -45	66	18	45-55	5

Add to Ref. N for Black

