

1900



Material: POLYAMIDE PA6.6
 self-extinguishing class V2 (UL 94)
 Temperature range:
 -20°C to +90°C (continuous)
 Sealing ring: NEOPRENE® 50 sh A
 Protection: IP 68
 Colour: RAL 7035 light grey,
 RAL 9005 black



MAXiblock[®] standard

BSP thread ISO 228/1

Ref.	P Light	Fixing Hole ∅ (mm)	∅ A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1900.14	G1/4"	13,5	3- 6,5	15	8	18-22	100
1900.38	G3/8"	17	4- 8	19	8	22-26	100
1900.12	G1/2"	21,5	7-12	24	10	24-29	100
1900.34	G3/4"	27	13-18	33	12	30-35	50

Add to Ref. N for Black

MAXiblock[®] specials

Pg thread DIN 40 430

Ref.	P Light	Fixing Hole ∅ (mm)	∅ A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
○*1920.09	Pg 9	15,5	5- 8	19	8	22-26	100
○*1921.09	Pg 9	15,5	5- 8	19	15	22-26	100
△ 1902.13N	Pg13.5	20,5	7-12	24	10	24-29	100
○ 1920.36	Pg36	47	20-32	53	14	42-49	25
○ 1921.36	Pg36	47	20-32	53	18	42-49	25

* Add to Ref. N for Black △ Add to Ref. N for Black ○ PVC sealing ring

