


Position and safety switches

KB plastic series and KM metal series limit switches dimensions to EN 50047

Top push rod plunger




KB A1 S, KB A1 A, KB A1 L
KM A1 S, KM A1 A, KM A1 L



M20 ENTRY

For types with 1/2 NPT entry, add the letter N at the end of the catalog number. E.g. KB A1 S11N



Contacts	Plunger material	Catalog number [Ⓜ] Plastic body	Metal body
1NO+1NC Snap action [Ⓛ]	Steel	KB A1 S11	KM A1 S11
2NC Snap action [Ⓛ]	Steel	KB A1 S02	KM A1 S02
1NO+1NC Slow break make before break [Ⓛ]	Steel	KB A1 A11	KM A1 A11
1NO+1NC Slow break [Ⓛ]	Steel	KB A1 L11	KM A1 L11
2NC Slow break [Ⓛ]	Steel	KB A1 L02	KM A1 L02
2NO Slow break	Steel	KB A1 L20	KM A1 L20
1NO+2NC Slow break [Ⓛ]	Steel	KB A1 L12	KM A1 L12
2NO+1NC Slow break [Ⓛ]	Steel	KB A1 L21	KM A1 L21
3NC Slow break [Ⓛ]	Steel	KB A1 L03	KM A1 L03

[Ⓛ] Direct (positive) operating operation \ominus ; safety function according to IEC/EN 60947-5-1.

[Ⓜ] Contact Sales & Technical Support for details and pricing.

General characteristics

The LOVATO ELECTRIC limit switches have been designed to satisfy requirements comprising quick installation, wiring ease, simple setup, modularity, sturdiness and constant reliability. The body cover has a captive closing screw and is hinged at the bottom and removable. The innovative locking bayonet mechanism consents to remove and reposition the operating head in the required configuration with no tools. The heads have axial rotation of 45° angles. The auxiliary contact blocks are removable assuring remarkable wiring simplicity. The heads are made of metal while the body housing of self-extinguishing polymer thermoplastic for the KB types or of aluminum-zinc alloy (zama) for the KM types.

Operational characteristics

- Maximum operating rate: 3600 cy/h
- Switching time: 0.5-1.5m/s
- Mechanical life: >10 million cycles
- Rated thermal current Ith: 10A
- UL designation: A600 Q300
- Rated insulation voltage Ui: 690V
- Rated impulse withstand voltage Uimp: 6kV
- Class II insulation
- Contact capacity: <10mΩ
- Short-circuit backup protection:
 - slow-blow fuse: 10A aM maximum admissible size
 - quick fuse: 16A gG maximum admissible size
- Wire connection: Self-releasing screw terminal
- Degree of protection:
 - IP20 for terminals
 - IP65 for body housing
- Operators of aluminum-zinc alloy
- Housing:
 - KB series - Self-extinguishing double-insulation polymer thermoplastic
 - KM series - Aluminum-zinc alloy
- Wire entry: M20 standard supplied; 1/2 NPT available (see the side note for details)
- Operating head fixing: Locking bayonet insert
- Operating force: 18 oz / 5N
- Operating temperature: -13° to +160°F (-25 to +70°C)
- Storage temperature: -40° to +160°F (-40 to +70°C)
- Pollution degree: 3 (suitable for dirty ambient).

Certifications and compliance

Certifications: cULus pending.
Compliant with standards: IEC/EN 60947-5-1, EN 50047, IEC/EN 60204-1, IEC/EN 60081-1.

- ▶ Forward travel of snap action contacts
- ◀ Return travel of snap action contacts

□ open
■ closed

